PRODUCT COMPARISON

FIFTH WHEEL RANGE	MATERIAL	USAGE	APPLICATION		IMPOSED (U) & D-VALUE T / KN	WEIGHT KG	HEIGHT OPTIONS MM (DIN 6)	LOW MAIN- TENANCE	SINGLE- POINT AUTOLUBE	AIR ACTIVATION	SINGLE SENSOR SAFETY CLIP	SENSOR SYSTEMS	HANDLE OP	TIONS	
150SP ²	Pressed	Standard duty 2" on-road	Fit for Flexible haulage volume carriers using two and three-axle tractors.		20T / 152kN	From 113kg	138 / 148 161 / 185 210 / 230 257	×	✓	✓	✓	✓	Standard with safety clip Extended with safety clip Interlock		•
3000	Cast	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silo, tank and volume carriers using both two and three-axle tractors.		20T / 150kN	From 120kg	138 / 148 161 / 185 210 / 230 257	×	✓	~	~	✓	Standard with safety clip Extended with safety clip Interlock		
3000LM	Cast	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silcarriers using both two and thr	o, tank and volume ee-axle tractors.	20T / 152kN	From 120kg	138 / 148 161 / 185 210 / 230 257	✓	✓	✓	✓	✓		with safety c	
3000FFH DUAL HEIGHT	Cast	Standard duty 2" on-road	Fit for Flexible haulage volume carriers using two and three-axle tractors.		18T / 130kN	335kg	167 / 267 317 / 367	✓	✓	~	✓	✓	Standard with safety clip Extended with safety clip Interlock		•
170CI	Cast	Heavy duty 2" on & off-road	Fit for HGV traffic and off-road terrain	ı.	25T / 170kN	From 140kg	148 / 161 185 / 210 230 / 257	×	✓	~	~	✓	Standard with safety clip Extended with safety clip Interlock		
260HD	Cast	Heavy duty 3.5" on & off-road 2" conversion available	Fit for HGV traffic and off-road terrain		36T / 260kN	From 216kg	190	×	✓	×	×	×	Standard	with safety c	lip
MOUNTING OPTIONS	USAGE	APPLICATION		IMPOSED(U) & D-VALUE T / KN	WEIGHT KG	HEIGHT MM	AIR / MANUAL	SLIDE TRAVEL	150SP ²	3000	3000LM	3000FFH	170CI	170HD	260HD
SLIDING 150SF	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage carriers using both two	e with silo, tank and volume o and three-axle tractors.	20T / 152kN	119kg	35mm	Air / Manual	Slide travel 525/750/900m Two-position 300/525mm	nm 🗸	✓	✓	×	✓	✓	✓
SLIDING 170SF	Heavy duty 2" on & off-road	Fit for HGV traffic and off-ro-	ad terrain.	25T / 170kN	241kg	40mm	Air / Manual	450mm	✓	/	✓	×	✓	✓	✓
MOUNTING PLATE	Medium duty 2" on-road & limited off-road		e with silo, tank and volume o and three-axle tractors.	20T / 150kN	45kg / 50kg	22mm 40mm	-	_	✓	~	~	×	✓	✓	✓
MOUNTING PLATE 260MP	Heavy duty 2" / 3" on & off-road	Fit for HGV traffic and off-roa	ad terrain.	36T / 260kN	89kg	16mm	Air / Manual	450mm	✓	/	✓	×	✓	✓	✓
DIRECT MOUNT	Standard duty 2" on-road	Fit for Flexible haulage volun using two and three-a:	ne carriers kle tractors.	20T / 150kN	40kg	140mm 160mm 200mm 230mm	-	_	~	~	✓	×	~	×	×